

6022/6024 High Temperature Calibration Oil Baths



产品概述: 6022/6024 High Temperature Calibration Oil Baths

Comparison calibrations require a heat source that's stable and uniform, and for moderately high temperatures nothing provides a better heat source than a Fluke Calibration oil bath.

Fluke Calibration oil baths are stable to $\pm 0.001^\circ\text{C}$ and do not require calibration blocks or use of special calibration techniques to achieve that stability. The specifications of all our baths are "true specifications representing the performance you can expect to achieve in your lab under your operating conditions. Other companies advertise specs that they know you will never see in your lab. When their baths fail to perform, they blame it on you.

Fluke Calibration baths are built using a unique tank design that guarantees the best uniformity possible in a liquid bath. This, coupled with the industry's best-selling digital bath controller, achieves uncompromised performance and ease of use.

Not only does our digital controller have features like its "Super-Tweak high-resolution mode so you can dial in the exact temperatures you want, it also lets you completely automate the calibration process using your PC and our 9938 MET/TEMP II software.

You'll love these baths, and once you've got one you'll never buy anything else. There's a bath to match any temperature range, depth, price, and performance you need.

产品规格: 6022/6024 High Temperature Calibration Oil Baths

型号



6024

本产品已停产或重新分类
标准槽，40°C 到 300°C，深

6022

本产品已停产或重新分类
标准槽，40°C 到 300°C，高容量

2001-IEEE

IEEE-488 接, 6330/7320/7340□

Fluke. 让您的工作畅通无阻。

福禄克测试仪器（上海）有限公司 电话：400-810-3435 ©2025 福禄克公司
06/2025

北京福禄克世禄仪器维修和服务有限公司 电
话：400-615-1563

未经许可，本文档禁止修改

福禄克测试仪器（上海）有限公司上海维修中心 电
话：021-54402301, 021-54401908分机269

福禄克测试仪器（上海）有限公司深圳第一特约维修点
电话：0755-86337229